

SpotOn®

SynTac™

ENVIRONMENTALLY FRIENDLY GRAPHICS

SpotOn® SynTac™ is a 4.8 mil (120µ) printable matte white, self-adhesive PP film with a dot pattern, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single-sided, siliconized Kraft PE coated release liner. This high quality, ink receptive white synthetic paper was specifically developed with the environment in mind. SpotOn® SynTac™ allows for easy, bubble-free application of vibrant graphics.

- IDEAL FOR "ENVIRONMENTALLY FRIENDLY" EASY TO INSTALL GRAPHICS
- GRAPHICS FOR SEASONAL PROMOTIONS APPLICATIONS
- SHORT-TERM WALL AND WINDOW APPLICATIONS



Drytac
Easy Green
Solution

Product Code: SPSF

120 White
micron Matte
PP



Latex
UV



Removable
DOT Pattern Polyacrylate
Adhesive



Width 1370mm

YEARS DURABILITY
2

INTERIOR

MONTHS DURABILITY
6

EXTERIOR



APPLICATIONS

- MOUNT TO BOARDS
- WINDOW GRAPHICS
- FLOOR GRAPHICS*
- TEMPORARY SALES SIGNAGE
- PRESENTATIONS
- POP & EVENT SIGNAGE



DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

SpotOn®

SynTac™

SpotOn® SynTac™ is a 4.8 mil (120µ) printable matte white, self-adhesive PP film with a dot pattern, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single-sided, siliconised Kraft PE coated release liner. This high quality, ink receptive white synthetic paper was specifically developed with the environment in mind. SpotOn® SynTac™ allows for easy, bubble-free application of vibrant graphics.

- IDEAL FOR "ENVIRONMENTALLY FRIENDLY" EASY TO INSTALL GRAPHICS
- GRAPHICS FOR SEASONAL PROMOTIONS APPLICATIONS

*To create a two part PVC-free floor graphic solution, simply pair SpotOn SynTac with Drytac Interlam EcoTex. This pair allows for easy, bubble-free application of vibrant slip-rated floor graphics. SpotOn SynTac paired with Drytac Interlam EcoTex was specifically developed with the environment in mind. SpotOn SynTac is a printable matte white, self-adhesive PP film with a SpotOn dot pattern, removable pressure sensitive polyacrylate adhesive. Interlam EcoTex is PP pressure sensitive overlaminating film with a pebble texture finish. Up to 1 year durability based upon foot traffic and proper installation.

**Please note: ink dependant for outdoor durability.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2023 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

04/2023

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte White PP
Adhesive	Removable Dot Pattern Polyacrylate
Release Liner	140 gsm 1 Side Siliconised PE Coated Kraft

PRODUCT CHARACTERISTICS

Film Thickness	4.8 mil (120µ)	} 5.3 mil (133µ)
Adhesive Layer	0.5 mil (13µ)	
Outdoor Durability	6 months**	
Application Temperature	>41°F (5°C)	
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)	
Shelf Life	1 year	
Storage Conditions	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity	

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com